



FIELDKING REVERSIBLE MOUNTED M.B. PLOUGH



BENEFITS:

- It can handle the toughest ploughing job with outstanding penetration performance.
- It is designed to work in all types of soil for basic functions such as soil breaking, soil raising and soil turning.
- It can be used in stony & rooted soils.

FEATURES:

- The under-frame and unit-to-unit clearance are adequate to cope with trashy conditions.
- Adding an extra furrow or repositioning units to allow for extra clearance is quick and easy.
- The plough has special wear-resistant steel bottoms with bar points for toughest ploughing jobs.
- Bar point bottoms ensure longer life as they can be extended or reversed and re-used till the last possible length.

SPECIFICATIONS:

CODE	MBP005F2	MBP005F3
SIZE	2 FURROW	3 FURROW
FRAME	115x115x10mm Box & 50 mm Round	115x115x10mm Box & 50 mm Round
TYNE	105x40mm Profile Cut Single Piece	105x40mm Profile Cut Single Piece
LENGTH	74 Inches	100 Inches
WIDTH	54 Inches	54 Inches
HEIGHT	54 Inches	54 Inches
BLADE	10mm	10 mm
MOULD BOARD	8 mm	8 mm
SHOVEL (POINT)	40x25 mm Bar (EN – 42 Forged)	40x25 mm Bar (EN – 42 Forged)
3 POINT LINKAGE / BEARING	75X20 mm Flat / 32017	75X20 mm Flat / 32017
ADJUSTMENT	Hydraulic	Hydraulic
WIDTH OF CUT (Between Tynes)	29 Inches	29 Inches
DEPTH OF CUT	350mm (max)	350mm (max)
WEIGHT	430 Kg. (approx)	575 Kg. (approx)
POWER REQUIRED (HP)	40-55	55-65

*The weight and working data contained in the present leaflet are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification/improvement.

Mfg. By:

BERI UDYOG PVT. LTD.

(AN ISO 9001-2000 COMPANY)

PLOT NO.100-101, SECTOR 3, HSIIDC, KARNAL (HARYANA) INDIA

PH: 00 91 184 2221571/72/73, FAX: 00 91 184 2221574

E-mail: info@fieldking.com, Homepage: www.fieldking.com